


LC-4300S: Your Best Value in Portable Multimedia.

KEY FEATURES:

- 450 ANSI Lumens light output at 90% uniformity, for brilliant images even in normal room light.
- 640 x 480 pixel resolution for VGA & MAC. Also, handles 800 x 600 VGA in compressed mode.
- Compact 21.8 lb. design with built-in carrying handle fits easily into airline overhead compartments.
- High performance lens with quick zoom and focus adjustments projects up to a 300" diagonal picture from distances up to 51.2'.
- Bonus! IR50 wireless remote mouse control and real-time Presentation F/X software.



LC-4300S SPECIFICATIONS:

Screen Brightness	450 ANSI Lumens
Illumination Uniformity	90%
Size of Color Palette	16.7 Million
Contrast Ratio	100 :1
Horizontal Resolution	550 TV Lines
Projection Lamp	200-Watt, Long-Life Metal-Halide
Light - RGB Distribution	Dichroic Mirror System
Imaging System	3 x 1.3" polysilicon TFT panels
Screen Pixels	640x480 = 307,200
Total Pixels	307,200 x 3 = 921,600
Lens Type	1:1.3 Manual Zoom and Focus
Lens Speed & Focal Length	f2.8-3.2, FL 53-69mm
Image Diagonal (Min-Max)	30" - 300"
Image Width (Tele: Min-Max)	2' ~ 20' (0.6m ~6.1m)
Throw Distance (Tele: Min-Max)	4.9' ~ 51.2' (1.5m ~ 15.6m)
Width-to-Throw Factor	Approx. 2.0 - 2.6
Elevation: Front	Adjustable up to 8 degrees
Image offset	Fixed, Up, Top/Bottom 9:1
Scanning	Auto: H Sync. 15~37.9kHz; V Sync. 50~70kHz
Image Orientation	Normal, Reversed, Inverted
Remote Control	Infrared
Computer Standards	VGA, EGA, CGA, MAC
Special Capabilities	800x600 SVGA(compressed)
Computer Channels	1

OTHER IMPORTANT FEATURES:

- Short-throw lens projects image sizes from 30 to 300 inches diagonal.
- High light output, long-life 200 -Watt, Metal Halide lamp.
- Included Accessories: Power Cord, Lens Cap, Dust Cover, Owner's Manual, VGA"Y" input cable and MAC "Y" input cable, VGA & MAC terminators, IR Projector Remote Control & Batteries, "RS-232" Computer Control Cable and Software, Bonus: IR50 Remote Mouse & Presentation F/X.
- Optional Accessories: 1.3x Tele Adapter, Soft Travel Case with wheels and telescoping handle. Soft Carry Bag. Hard Shipping Case. Ceiling Mount, MAC Monitor Cable.

SPECIFICATIONS (cont.)

Computer Inputs	Supplied VGA& MAC Cable to HDB 15 x 1
Computer Monitor Out	HDB 15 x 1
Computer Audio In	RCaX 2 (L/R)
Video Standards	NTSC/PAL/SECAM/NTSC 4.43
Video Channels	1
Video Input	RCaX 1, BNC x 1, S-Video x 1
Video Output	RCA x 1
Video Audio Input	RCA x 2
Audio - Amplifier	3 Watts RMS mono (THD 10%)
Audio - Built-in Speaker	2" x 3.5" (5cm x 9cm) x 1
Audio - Audio Monitor	RCaX 2 (L/R)
Audio - Speaker Output	MiniJack x 1
Fan Noise Level	Less than 48.5 dB
Size (HxWxD)	6.2" x 16.8" x 15" (158 x 430 x 385 mm)
Weight	21.8 Lb. (9.9 kg)
Power Requirements	120V 50/60 Hz
Power Consumption	285 Watts
Power Cord	10'(3M) Type 3, Detachable
Safety Compliance	UL Listed
Warranty - Projector	1 Year Parts & Labor
Warranty - Lamp	3 Months, Free Replacement

Specifications subject to change without notice.

©1998 EIKI International, Inc. Printed in the USA. 1/28/98

EIKI

A-Key to better communications.